QUARTZ CRYSTAL



OCXO 14 x 9 mm Dip Type Series



产品特点


. 基站和无线通信中的应用。

Features


. For base station and wireless communication application.


| 电气规格 Electrical Specifications | |
|--------------------------------------|--|
| Item/Type | Description |
| 尺 寸 Dimension | 14x9 mm Typ. |
| 标称频率 Nominal Frequency [#1] | 10, 19.2, 20MHz |
| 输出类型 Output Type [#2] | CMOS |
| 输出负载 Output Load | 15pF,Typ. |
| 电源电压 Supply Voltage (Vcc) | 3.3V |
| 功率消耗 Power Consumption | 3.0 W Max. While Warm-Up , 1.25 W Max. at Steady State |
| 预热时间 Warm-up Time | 5 Minutes Typ. |
| 初始容差 Initial Tolerance | ±0.2 ppm Max. |
| 工作温度 Operating Temperature Range[#4] | - 40 to + 85 ℃ |
| 控制电压 Control Voltage Range (Vc) [#5] | 0 to 3.3 V |
| 频率牵引 Frequency Pulling Range | ±1.0 ppm Typ. |
| 线 性度 Linearity | 10% Max. |
| 电压参考 Voltage Reference | NA |

尺寸图 Dimensions



Pin function:
Pad 1:Vc
Pad 2:N.C
Pad 3:GND
Pad 4:Output
Pad 5:N.C
Pad 6:Vcc





物料编码 Material code

TEL: 0579-88623156

网址: www.lucki.com.cn